



## DIGITAG LR Hands-Free Access Control (Active Tag)

Digitag LR is an innovative product offering users real “hands-free” access control at affordable prices.

Digitag LR is ideally suited for use in hospitals, residential homes, parking lots, gates or simply where the convenience of hands-free access control is preferred. The range adjustment, together with the ease of installation and the flexibility of being industry compatible has made Digitag LR a leader in this field. Clever innovation has removed the traditional objections of hands-free active tags (battery life and cost). By providing a changeable battery, the tags do not have a limited life so under normal wear & tear conditions they will provide many years of activity.

### Receiver:

Voltage:	12-30Vdc
Current:	40mA
Frequency:	433.92MHz
IP range:	IP 55 (Water resistant, design for outdoor installation)
Operating temperature:	-25°C to +55°C
Adjustable Range:	From 1M to 15M (3 ft to 50 ft)
LED:	1 green, 1 red
Output 1:	Wiegand 26 Bit
Tags in field:	20
Dimensions:	90 x 60 x 22mm (3.5 x 2.4 x .9 in)

### Transmitters:

Supply:	3V
Battery:	One Lithium battery CR2032
Frequency:	433.92MHz
Dimensions:	70 x 35 x 9mm (2.75 x 1.4 x .35 in)



Receiver  
DTRR1434



1-Button  
Transmitter  
(Transmit  
on demand or  
continually)  
DTXT1434

Active  
Transmitter  
(Transmit  
continually)  
DTXT0434



Specifications may change  
without prior notice.

Visit our web site to consult the installation manual: [cdvi.ca](http://cdvi.ca)