



www.cdvi.ca

PROMI1000 / PROMI1000 PC 1-Door Stand-Alone Proximity Reader and Keypad

- 1000 programmable proximity badges and 1000 user codes
- 3 operating modes:
 - Mode 0: badge and code
 - Mode 1: badge only
 - Mode 2: badge or code
- Audible & Visual feedback
- 1000 event memory
- 16 holiday schedules
- Real-time event printing
- Anti-passback
- 1 request-to-exit input
- Tamper switch
- Input voltage: 12VAC/DC
- 1 form C, door relay output (3A/125V)
- 1 form C, alarm relay output (3A/125V)
- Current consumption: 300mA
- Manage by PC (PROMI1000 PC only)



Proximity Reader Built-in

Optional remote readers for PROMI1000 and PROMI1000PC:

(Up to 50M (164ft) between the reader and the controller):

DGLP / DGLP/F | Proximity Reader

DGLP/F



- Surface mount polycarbonate
- Reader range up to 8cm (3.5")
- LED visual feedback
- Input voltage: 12V ac/dc

DGLI / DGLI/F | Proximity Reader

DGLI/F



- High Resistance to Vandalism
- Reader range up to 10cm (4")
- 4 pair cable wiring
- LED visual feedback
- Input voltage: 12V ac/dc

DGLIE | Flush Mount Proximity Reader



- Stainless steel flush mount proximity reader
- Dust/Weather/Vandal resistant
- Reader range up to 15cm (6")
- Power requirements: 12Vdc

DGLP/60 | Long Range Proximity Reader



- Polycarbonate
- Reader range up to 60cm (23.6")
- Red/Green LEDs and Buzzer
- Power requirements: 12Vdc

DGLP/T | Proximity Reader



- Specifically designed to be mounted on door frames or on audio entry panels
- Read range 6cm
- 25 mm mounting hole
- Input voltage: 12V AC/DC

Proximity Cards and Badges

- BP:** Elegant leather key ring badge
- CPE:** Standard clamshell card
- CP:** Thin card for printing photos and text (ISO)
- PPC:** Rugged gray polycarbonate key ring badge
- PP:** Stylish black polycarbonate tear drop badge

Specifications may change without prior notice. Printed in Canada - 26/03/08